

HOU-WM6010 Metal detector



Features:

Specification

Display	LCD display
Boot self-check function	After booting, the system will automatically diagnose to confirm if the equipment running condition is normal or not. (2) System failure content will automatically display if there is a breakdown.
Operating system	Chinese/English menu option
Passing speed	The detection speed can be adjusted from the fastest 100 persons / minute(custom detection speed adjustment).
Background light time	0-99s. Display time can be continuous adjustable
Calendar	Display of year, month, day, minute.
Detection zones	5 detection zones
Alarm indication	(1) 1-25 s alarm time, 255 volumes can be adjusted continuously. (2) LED light alarming zone directly and accurately shows the location of prohibited body hidden item in corresponding height.
Sensitivity adjustment	(1) 255 sensitivity levels can be adjusted for homogeneous detection zones(three usage modes in different occasions.

Product Specifications:

• **Model : HOU-WM6010**

Performance of anti-jamming	(1) Adopt temperature and humidity automatically detecting and tracking compensation technology, to adapt to different environments and climates to significantly improve the anti-interference ability. (2) Adjustable frequency, range from 4Khz to 8 Khz, to overcome outside interference by same frequency products.
Safety performance	(1) Adopt double protection passwords, only allow authorized personnel to operate, with higher security. (2) With factory setting restoring function in case of system errors caused by inadvertent operation by users. (3) Adopting uninterrupted power supply protection system, power battery lasts for 2-8 hours, the system has protection function for parameters (optional). (4) The power supply, at the bottom of the door, 12 v low voltage power supply, can be controlled by the operation panel, moisture-proof, waterproof and heat- dissipated. (5) Harmless to apparatus of cardiac pacing in human body, pregnant women, magnetic floppy disks, tapes, etc
Dry Contact	Able to work with access control systems
Tally function	Intelligent traffic counting and alarm functions, automatically statistics of the amount of pass and the number of alarms.
Operation place	Application: airports, places of entertainment, courts, etc.)
Power supply	Input AC85V ~ 264 v / 50-60 hz, adapter 12 v, power supply output current 3 a
Power	20 w, low power consumption, low radiation
Size	2000 mm (height) X400mm (widty) X120mm (thickness)
Detection distance	40-70cm
Weight	35kg
Operating environment	-20 ℃- +45 ℃
Standard	-With Inspection report by the Ministry of Public Security. -With registered trademark. -With appearance patent and utility model patent, no involve the use of intellectual property disputes. -Harmless to pregnant women and magnetic medium floppy disks, tapes, video, etc. conforming to "GB15210-2003".