

Product datasheet

Specifications



Power supply module,
SpaceLogic, 24VAC or 21-30VDC,
for AS-P and I/O modules

SXWPS24VX10001

Main

Range	EcoStruxure Building Operation
Device short name	PS-24V
Product brand	Schneider Electric
Product or component type	Power supply module

Complementary

Range compatibility	EcoStruxure Building Operation AS-P controller EcoStruxure Building Operation TB-PS-W1 terminal base
Secondary power	10 W 24 V AC 10 W 21...30 V DC
Width	90 mm
Depth	64 mm
Height	114 mm
Quantity per set	1

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	5.6 cm
Package 1 Width	11.7 cm
Package 1 Length	9.0 cm
Package 1 Weight	211.6 g

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Sustainability

Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)



Transparency RoHS/REACH

Well-being performance

✓ Mercury Free

✓ Rohs Exemption Information [Yes](#)

✓ Pvc Free

✓ Halogen Free Plastic Parts & Cables Product

Certifications & Standards

Reach Regulation [REACH Declaration](#)

Eu Rohs Directive Compliant with Exemptions

China Rohs Regulation [China RoHS declaration](#)

Environmental Disclosure [Product Environmental Profile](#)

Weee The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Circularity Profile [End of Life Information](#)