# **Product data sheet**

Specifications



# InRow RC, 600mm, Chilled Water 380-415V 50/60 Hz, w/ humidifier

ACRC602P

Overview	
Lead time	Special Order - Call for Quoted Lead Times
Main	
Main Input Voltage	380 V 3 phases 415 V 3 phases
Number of rack unit	42U
Number of cables	2
Provided equipment	Installation guide Operations and maintenance manual
General	
Humidification flow	2.99 kg/hr
Air discharge option	Horizontal
Intake air option	Rear return
Air flow	2831.68 l/s
Minimum water inlet temperature	7 °C
Condensate pump flow	0.03 m3/h
Dhusical	
Physical	
Colour	Black
Height	199.1 cm
Width	60 cm
Depth	107 cm
Net weight	352.73 kg
Mounting preference	No preference
Mounting mode	Not rack-mountable
Input	
Input power	15000 W
Network frequency	50 Hz +/- 3 Hz
Number of input connectors	1 hard wire 4-wire (3P + E)



### Conformance

Product certifications	cUL listed GOST Industry Canada
Standards	FCC part 15 class A

# **Communications & Management**

Control panel	Multifunction LCD status and control console
Alarm	Audible and visible alarms prioritized by severity

# **Packing Units**

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	216.6 cm
Package 1 Width	113.7 cm
Package 1 Length	85 cm
Package 1 Weight	463.18 kg
Number of Units in Package 3	1

#### **Offer Sustainability**

EU RoHS Directive	Not applicable, out of EU RoHS legal scope
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

#### **Contractual warranty**

Warranty

1 year (parts only), 1 year on-site repair or replace with factory authorized Start-Up

Recommended replacement(s)